



# Application Detail Form P-700 RVP Analyzer

4724 S. Christiana Ave., Chicago, Illinois 60632, USA    773 927 8600(phone)    773 927 8620 (facsimile)

Contact: \_\_\_\_\_  
 Title: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 City, State ZIP: \_\_\_\_\_  
 Country: \_\_\_\_\_  
 Phone: \_\_\_\_\_  
 Fax: \_\_\_\_\_  
 Email: \_\_\_\_\_

Desired Delivery Date: \_\_\_\_\_  
 Refinery: \_\_\_\_\_  
 Area: \_\_\_\_\_  
 City: \_\_\_\_\_  
 State: \_\_\_\_\_  
 Country: \_\_\_\_\_

If replacing an existing analyzer what is being replaced?

Analyzer Manufacturer:		Analyzer Model:	
------------------------	--	-----------------	--

Please Describe the Application (i.e. process stream and monitoring objectives):

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**Laboratory Test Method** \_\_\_\_\_ **will be used to correlate with the new on-line analyzer.**

### Sample Data:

Analyzer	Unit of Measure	Normal	Maximum	Minimum
RVP Range:	psi / bar			
Viscosity:	cP @ process temperature			
Water:	%		N/A	N/A
Solids:	PPM		N/A	N/A
Dissolved Solids:	%		N/A	N/A

**Sample Contaminants (Describe):**

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Sample Slipstream Limits:

Inlet to Analyzer: \_\_\_\_\_ barg / psig at \_\_\_\_\_ °C / °F  
 Return Tap from analyzer: \_\_\_\_\_ barg / psig  
 Distance from analyzer to process tap: \_\_\_\_\_ meters / feet to return tap: \_\_\_\_\_ meters / feet

Additional Notes:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

**ORB Instruments, Inc.**

4724 South Christiana - Chicago, Illinois 60632 - USA  
 773.927.8600 Phone - 773.927.8620 Fax - www.orbinstruments.com



**Electrical Power Supply:**

\_\_\_\_\_ Volts AC \_\_\_\_\_ +/- Volts AC \_\_\_\_\_ Hz \_\_\_\_\_ Phase

**Output Signal:**

One 4-20 mA output signal is standard

Output Range (minimum): \_\_\_\_\_ (maximum): \_\_\_\_\_

**Area Classification** (please check one):

- NEC Class 1, Div. 1, Group C & D
- ATEX Zone 1 II B + H2 T4
- General Purpose Area

**Area Protection Preference** (please check one):

- Nitrogen Purged
- Explosion Proof

**Nitrogen Supply (Purged Units):**

Standard requirement is better than 98% pure with minimum pressure of 2.7 bar (40 psi) and maximum pressure of 6.8 bar (100 psi); Expected leakage compensation is 1 l/min

**Environment:**

Temperature range inside analyzer shelter (minimum): \_\_\_\_\_ °C / °F (maximum): \_\_\_\_\_ °C / °F

Expected humidity inside analyzer shelter: \_\_\_\_\_ %

Will analyzer be subjected to a tropical climate: \_\_\_\_\_ Yes \_\_\_\_\_ No

Special environmental requirements (describe): \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Commissioning & Start-up:**

Do you or the end-user request commissioning & start-up assistance: \_\_\_\_\_ Yes \_\_\_\_\_ No

If yes, please detail: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Process Sample Supplied:**

Customer Supplied: \_\_\_\_\_ Yes \_\_\_\_\_ No      Product Name: \_\_\_\_\_

If No, please explain: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Approval:**

Completed by: \_\_\_\_\_  
Signature

\_\_\_\_\_

Print Name

\_\_\_\_\_

Title

Approved by: \_\_\_\_\_  
Signature

\_\_\_\_\_

Print Name

\_\_\_\_\_

Title